


STABILO® System

Mobile Scaffold Series 100

- TUEV approved, load capacity 200 kg/m² (scaffold class 3) in accordance with EN1004
- The universal aluminum scaffold for working heights of up to 14.00 m
- The assembled scaffold is easily moved on the cross bar
- Height-adjustable castors ensure safe use on uneven terrain
- The platform panels may be easily mounted (in increments of 25 cm) between the diagonal rods. No more reassembly or disassembly!
- Extension arms are included in the delivery for all scaffolds with a working height of 7.40 m or above
- Field lengths: 2.00 m, 2.50 m and 3.00 m
- Scaffold field width: 0.75 m

You can find System parts from page 84



Important: Depending of the mobile scaffold configuration, ballast weights must be used (accessories). For ballast weight specifications, please refer to the instructions for assembly and use or at our homepage.

73 100		Field length: 2,00 m - Scaffold platform width: 0,75 m								
Working height	ca. m A	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40
Standing height	ca. m B	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40
Scaffold height	ca. m C	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40
Total weight	kg	116,0	127,0	134,0	178,0	192,0	216,0	227,0	254,0	266,0
Art.-No.		731050	731067	731074	731081	731098	731104	731111	731128	731135

74 100		Field length: 2,50 m - Scaffold platform width: 0,75 m										
Working height	ca. m A	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40	14,40
Standing height	ca. m B	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40
Scaffold height	ca. m C	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40
Total weight	kg	127,0	141,0	148,0	197,0	214,0	238,0	252,0	284,0	298,0	305,0	319,0
Art.-No.		741059	741066	741073	741080	741097	741103	741110	741127	741134	741141	741158

75 100		Field length: 3,00 m - Scaffold platform width: 0,75 m										
Working height	ca. m A	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40	14,40
Standing height	ca. m B	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40
Scaffold height	ca. m C	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40
Total weight	kg	143,0	158,0	165,0	225,0	246,0	270,0	284,0	328,0	343,0	350,0	365,0
Art.-No.		751461	751560	751669	751768	751867	751966	751065	751164	751263	751362	751409