



Crossovers (light metal)

- Stationary or mobile working appliance for all applications where obstacles must be safe crossed according the regulations of EN ISO 14122
- Standard depth of platform: 700 mm, extension and widening on request available
- Width of steps: 600 - 800 - 1000 mm
- Aluminium grating / perforated steps on request
- Delivery with hand rail on one side and railing (second hand rail and railing available for extra charge)
- Hand rails are equipped with a knee rail by stairs with inclination of 45°
- Platform railing 1100 mm high and equipped with knee and foot rails
- Mobile execution are equipped with 2 stable stabilizer gears and 4 casters (between the ascending parts, 2 longitudinal braces essential)
- Stationary execution are equipped with fastening brackets
- The below-mentioned chart corresponding the stationary execution, mobile crossovers on request
- Delivery in pre-assembled component groups
- For all orders indicate the clearance height (dimension I at the right draft)

Inclination 45°

No. of steps		4	5	6	7	8	9	10
Clearance height I	mm	608 - 822	823 - 1037	1038 - 1252	1253 - 1467	1468 - 1682	1683 - 1897	1898 - 2112
Platform length A	mm	700	700	700	700	700	700	700
Projection D	mm	1892 - 2321	2322 - 2751	2752 - 3181	3182 - 3611	3612 - 4041	4042 - 4471	4472 - 4901
Step width B 600 mm	Art.-No.	826039	826046	826053	826060	826077	826084	826091
Step width B 800 mm	Art.-No.	826237	826244	826251	826268	826275	826282	826299
Step width B 1000 mm	Art.-No.	826435	826442	826459	826466	826473	826480	826497
Second hand rail for extra charge available	Art.-No.	826633	826640	826657	826664	826671	826688	826695

Inclination 60°

No. of steps		4	5	6	7	8	9	10
Clearance height I	mm	713 - 962	963 - 1212	1213 - 1462	1463 - 1712	1713 - 1962	1963 - 2212	2213 - 2462
Platform length A	mm	700	700	700	700	700	700	700
Projection D	mm	1507 - 1795	1796 - 2084	2085 - 2373	2374 - 2661	2662 - 2950	2951 - 3239	3240 - 3527
Step width B 600 mm	Art.-No.	826831	826848	826855	826862	826879	826886	826893
Step width B 800 mm	Art.-No.	827036	827043	827050	827067	827074	827081	827098
Step width B 1000 mm	Art.-No.	827234	827241	827258	827265	827272	827289	827296
Second hand rail for extra charge available	Art.-No.	827432	827449	827456	827463	827470	827487	827494

Variant steps execution:

Step width B mm		600	800	1000
Step execution steel grating	Art.-No.	823908*	823915*	823922*
Step execution steel perforated	Art.-No.	823939*	823946*	823953*
*Extra charge per step				

Platform extension

Step width B mm		600	800	1000
Platform extension, aluminium 215 mm*	Art.-No.	827609	827616	827623
Railing extension, aluminium 215 mm	Art.-No.	827630	827630	827630
*Maximum platform extension 3010 mm				

Mobile execution:

Mobile execution	Art.-No.	827708
Consists of: 2 stabilizers and 4 casters (Ø 160 mm)		
In addition, two longitudinal braces between the ascending parts essential		

On request for special constructions please indicate:

Steps

- Aluminium corrugated (standard)
- Steel grating
- Steel perforated

No. of steps _____ pc.

Dimensions

- Work inclination α : _____ °
- Step width B: _____ mm
- Step depth W: _____ mm
- Platform length A: _____ mm
- Clearance height, inside I: _____ mm
- Clearance width, top inside H: _____ mm
- Clearance width, bottom inside G: _____ mm
- Projection (if work inclination unknown) D: _____ mm
- Exterior width of stairs including railing F: _____ mm

Hand rail / railing:

- Complete hand rail left
- Complete hand rail right
- Platform railing left
- Platform railing right

Accessories with extra charge:

- Crossover with 2 stabilizers and 4 casters (Ø 160 mm)

Other requests: _____

