



Aluminum Chimney Sweeper Ladder

- Rails and rungs are made of aluminum
- Heavily profiled, half-round rungs
- Due to its half-round rung design, the ladder can be used for various roof pitches
- The ladders may be used only up to a roof pitch of 75°
- A 90 mm high side rail ensures a minimum rung-roof distance of 60 mm
- Extendable with strap connections
- GS-approved through the Trade Association
- Available in the following colours: Aluminum, red, brown and anthracite

Note: Roof safety hooks in accordance with DIN EN 517. For the first ladder, 2 roof hooks are required. To be hung into the second rung from above (see indentation) and at the lowest rung in order to prevent sidewise sliding. For each additional roof ladder to be linked, at least one roof hook is needed.

Colours:

- 1) Aluminum
- 2) Red (RAL 8004)
- 3) Brown (RAL 8014)
- 4) Anthracite (RAL 7016)



Ladder length	ca. m	2,00	2,80	3,95
Ladder width	ca. m	0,34	0,34	0,34
No. of rungs		7	10	14
Art.-No. (Aluminium-nature)		804617	804624	804631
Art.-No. (red)		804679	804686	804693
Art.-No. (brown)		804730	804747	804754
Art.-No. (anthracite)		804792	804808	804815

