



## Crossovers (light metal)

- Stationary or mobile working appliance for all applications where obstacles must be safe crossed according the regulations of EN ISO 14122
- Standard depth of platform: 645 mm, extension and widening on request available
- Width of steps: 600 - 800 - 1000 mm
- Aluminium grating / perforated steps on request
- Delivery with hand rail on one side and railing (second hand rail and railing available for extra charge)
- Hand rails are equipped with a knee rail by stairs with inclination of 45°
- Platform railing 1100 mm high and equipped with knee and foot rails
- Mobile execution are equipped with 2 stable stabilizer gears and 4 casters (between the ascending parts, 2 longitudinal braces essential)
- Stationary execution are equipped with fastening brackets
- The below-mentioned chart corresponding the stationary execution, mobile crossovers on request
- Delivery in pre-assembled component groups
- For all orders indicate the clearance height (dimension I at the right draft)

### Inclination 45°

No. of steps		4	5	6	7	8	9	10
Clearance height I	mm	560 - 760	761 - 960	961 - 1160	1161 - 1360	1361 - 1560	1561 - 1760	1761 - 1960
Platform length A	mm	645	645	645	645	645	645	645
Projection D	mm	2000	2400	2800	3200	3600	4000	4400
Step width B 600 mm	<b>Art.-No.</b>	<b>826039</b>	<b>826046</b>	<b>826053</b>	<b>826060</b>	<b>826077</b>	<b>826084</b>	<b>826091</b>
Step width B 800 mm	<b>Art.-No.</b>	<b>826237</b>	<b>826244</b>	<b>826251</b>	<b>826268</b>	<b>826275</b>	<b>826282</b>	<b>826299</b>
Step width B 1000 mm	<b>Art.-No.</b>	<b>826435</b>	<b>826442</b>	<b>826459</b>	<b>826466</b>	<b>826473</b>	<b>826480</b>	<b>826497</b>
Second hand rail for extra charge available	<b>Art.-No.</b>	<b>826633</b>	<b>826640</b>	<b>826657</b>	<b>826664</b>	<b>826671</b>	<b>826688</b>	<b>826695</b>

### Inclination 60°

No. of steps		4	5	6	7	8	9	10
Clearance height I	mm	696 - 940	941 - 1185	1186 - 1430	1431 - 1675	1676 - 1920	1921 - 2165	2166 - 2410
Platform length A	mm	645	645	645	645	645	645	645
Projection D	mm	1640	1910	2180	2450	2720	2990	3260
Step width B 600 mm	<b>Art.-No.</b>	<b>826831</b>	<b>826848</b>	<b>826855</b>	<b>826862</b>	<b>826879</b>	<b>826886</b>	<b>826893</b>
Step width B 800 mm	<b>Art.-No.</b>	<b>827036</b>	<b>827043</b>	<b>827050</b>	<b>827067</b>	<b>827074</b>	<b>827081</b>	<b>827098</b>
Step width B 1000 mm	<b>Art.-No.</b>	<b>827234</b>	<b>827241</b>	<b>827258</b>	<b>827265</b>	<b>827272</b>	<b>827289</b>	<b>827296</b>
Second hand rail for extra charge available	<b>Art.-No.</b>	<b>827432</b>	<b>827449</b>	<b>827456</b>	<b>827463</b>	<b>827470</b>	<b>827487</b>	<b>827494</b>

### Variant steps execution:

Step width B mm		600	800	1000
Step execution steel grating	<b>Art.-No.</b>	<b>823908*</b>	<b>823915*</b>	<b>823922*</b>
Step execution steel perforated	<b>Art.-No.</b>	<b>823939*</b>	<b>823946*</b>	<b>823953*</b>
*Extra charge per step				

### Platform extension

Step width B mm		600	800	1000
Platform extension, aluminium 215 mm*	<b>Art.-No.</b>	<b>827609</b>	<b>827616</b>	<b>827623</b>
Railing extension, aluminium 215 mm	<b>Art.-No.</b>	<b>827630</b>	<b>827630</b>	<b>827630</b>
*Maximum platform extension 3010 mm				

### Mobile execution:

Mobile execution	<b>Art.-No.</b>	<b>827708</b>
------------------	-----------------	---------------

Consists of: 2 stabilizers and 4 casters (Ø 160 mm)

In addition, two longitudinal braces between the ascending parts essential



**On request for special constructions please indicate:**

**Steps**

- Aluminium corrugated (standard)
- Steel grating
- Steel perforated

No. of steps \_\_\_\_\_ pc.

**Dimensions**

- Work inclination : \_\_\_\_\_ °
- Step width B: \_\_\_\_\_ mm
- Step depth W: \_\_\_\_\_ mm
- Platform length A: \_\_\_\_\_ mm
- Clearance height, inside I: \_\_\_\_\_ mm
- Clearance width, top inside H: \_\_\_\_\_ mm
- Clearance width, bottom inside G: \_\_\_\_\_ mm
- Projection (if work inclination unknown) D: \_\_\_\_\_ mm
- Exterior width of stairs including railing F: \_\_\_\_\_ mm

**Hand rail / railing:**

- Complete hand rail left
- Complete hand rail right
- Platform railing left
- Platform railing right

**Accessories with extra charge:**

- Crossover with 2 stabilizers and 4 casters (Ø 160 mm)

**Other requests:** \_\_\_\_\_  
 \_\_\_\_\_

