



Fixed Ladder, single section

- Available in natural and anodized aluminum, galvanized and in stainless steel in accordance with 18799 and DIN 14094, BGV D 36 and EN ISO 14122-4
- Aluminum model: grooved rungs 30 x 30 mm
- Steel model: perforated rungs 30 mm
- Outer ladder width: 520 mm
- Delivery in disassembled parts
- Easy assembly by screwed connections
- Assembly instruction enclosed
- For climbing heights exceeding 5 meters, back protection is included in the delivery
- Dowels and screws for wall attachment are not included in the scope of delivery. The ground must have sufficient load capacity
- For more accessories, see pages 49 - 51



Attention: BGV D 36 must be observed in accordance with DIN 18799 and 14094 and EN ISO 14122-4:

- In accordance with EN ISO 14122-4, a back protection is required for climbing heights of 3 m or more
- For every 2 meters, fixed ladders must be attached with wall anchors
- Maximum length of a multi-section ladder is 10 meters and a back guard is mandatory
- Systems with a climbing height exceeding 10 m require the use of intermediate platforms (if this is not possible, rest platforms must be installed every 10 m)
- If escape ladders in accordance with DIN 14094 are planned, the competent fire authority must be contacted, and the proper assembly and load bearing capacity must be checked and certified by an authorized inspector for stability
- As an economical and safe alternative for the back protection basket, refer to page 53 for our safety fall protection system which is in compliance with EN 353 and DIN 18799.

Standard elements included in the scope of delivery:	Aluminum, anodized	Aluminum, natural	Steel, galvanized	Stainless Steel V4A(1.4571)
	Art.-No.	Art.-No.	Art.-No.	Art.-No.
Ladder part 1,96 m	813138	813190	813251	813329
Ladder part 2,80 m	813145	813206	813268	813336
Ladder part 3,64 m	813152	813213	813275	813343
Exit rail on one side	813169	813220	813282	813350
Horizontal band (ø 700 mm)	816962	816979	816986	816993
Vertical bar (length 3000 mm)	816924	816931	816948	816955
Wall anchor, rigid (distance to wall 200 mm)	-	-	813312	813381

Climbing height to ca. m		3,92	4,76	5,60	6,44	7,28	8,40	9,52	9,80
Ladder length (incl. exit rail) ca. m		5,18	6,02	6,86	7,70	8,54	9,66	10,78	11,06
Aluminum, anodized	Art. -No.	833389	813398	813404	813411	813428	813435	813442	833426
Aluminum, natural	Art. -No.	833396	813459	813466	813473	813480	813497	813503	833433
Galvanized steel	Art. -No.	833402	813510	813527	813534	813541	813558	813565	833440
Stainless steel V4A (1.4571)	Art. -No.	833419	813572	813589	813596	813602	813619	813626	833457
Ladder part 1,96 m		2	1	-	-	-	-	2	5
Ladder part 2,80 m		-	1	2	1	-	3	2	-
Ladder part 3,64 m		-	-	-	1	2	-	-	-
Exit rail		2	2	2	2	2	2	2	2
Wall anchor, rigid (distance to wall 200 mm)		6	6	8	8	8	10	12	12
Horizontal band (ø 700 mm)		-	-	4	5	5	6	7	7
Vertical bar (length 3000 mm)		-	-	7	10	10	12	15	15

