




## Platform Stairs, mobile (Light Metal)

- Mobile platform stairs made of stable rectangular profile
- Inclination: 45°
- Width of steps: 600 - 800 - 1000 mm
- Corrugated, 215 mm width aluminium steps guarantee safe ascending and stable foothold
- Standard platform depth 645 mm, extension and widening available on request
- Easy movement through 2 casters (ø 150 mm) at the supporting part
- Aluminium grating / perforated steps on request
- Delivery in pre-assembled component groups
- On request without casters, therefore with 4 fastening brackets available

### Note:

According to EN ISO 14122-3, a railing is required for platform height starting with 0.50 m



<b>Work. height</b>	ca. m <b>A</b>	2,40	2,60	2,80	3,00
<b>Platform height</b>	ca. m <b>B</b>	0,40	0,60	0,80	1,00
<b>Projection</b>	ca. m	0,95	1,15	1,35	1,55
<b>Art.-No. (Step width 600 mm)</b>		810335	810342	810359	810366
<b>Art.-No. (Step width 800 mm)</b>		810373	810380	810397	810403
<b>Art.-No. (Step width 1000 mm)</b>		810410	810427	810434	810441
<b>One hand rail with railing</b>		818508	818515	818522	818539

<b>Step width mm</b>		600	800	1000
<b>Platform extension, aluminium 215 mm*, Art.-No.</b>		818607	818614	818621
<b>Forehead railing, Art.-No.</b>		818638	818645	818652
<b>Step execution, steel grating Art.-No.</b>		818546	818553	818560
<b>Step execution, steel perforated Art.-No.</b>		818577	818584	818591

Railing extension, 215 mm, Art.-No. 818669. \* maximum platform extension 3010 mm



Art.-No. 810366