



ProTec[®] XS-P System

Platform Scaffold (Aluminum)

- The ideal scaffold for extensive assembly and renovation works
- The large platform dimension (ca. 3.6m²) offers a lot of space for materials, tools personnel and is adjustable in 25 cm rung increments
- TÜV/GS approved, max. load of the platform space 650 kg according to EN 1004
- The platform is made of weatherproof and non-slip phenolic resin pane
- Quick assembly without use of tools thanks to rigid and guided bracing and slip-on modular frame elements
- 8 casters with brakes
- Useable as two separate foldable scaffolds

Important: Depending of the mobile scaffold configuration, ballast weights must be used (accessories). For ballast weight specifications, please refer to the instructions for assembly and use or at our homepage.

Work. height up to ca. m A		2,90	3,70
Standing height ca. m B		0,90	1,70
Scaffold height ca. m C		1,80	2,80
Article list	Art.-No.	920201	920218
Foldable unit (vertical frame + folding frame)	915009	2	2
Caster ø 125 mm	714107	8	8
Platform with hatch 2,00 x 0,60 m	911018	3	2
Platform without hatch 2,00 x 0,60 m	911001	-	1
Vertical frame 1,00 m	915023	-	4
Rail brace	912206	-	2
Climbing aid / connecting railing	911247	2	2
Total weight kg		89,4	106,4

