



STABILO®

Leaning Rung Ladder

- One piece lightweight and flexible aluminum rung ladder for daily industrial use
- Non-slip, 2-component footcaps: The hard component ensures a strong connection of the cap with the rail; the soft component provides a strong surface stiction and prevents slipping of the ladder
- Rails made of extruded aluminium profiles
- Completely profiled large dimensioned rungs for safe ascent and descent

For the **CombiSystem** (Safety Accessories) and other accessories refer to page 112.

Suitable for this ladder: **CombiSystem** 1, 2, 3, 4, 5, 6, 8



Certificate
EN 131
Norm

Work. height up to ca. m A	3,10	3,90	4,70	5,50	6,30	6,88	7,42	7,96	
Ladder length ca. m C	1,85	2,70	3,55	4,40	5,20	5,80	6,36	6,92	
No. of rungs	6	9	12	15	18	20	22	24	
Weight ca. kg	3,1	4,5	5,9	7,3	8,7	10,5	13,0	13,5	
Transport dimensions	Length ca. m	1,86	2,70	3,55	4,40	5,22	5,80	6,36	6,92
	Width ca. m	0,36	0,36	0,36	0,36	0,36	0,36	0,36	0,36
	Height ca. m	0,07	0,07	0,07	0,07	0,07	0,08	0,08	0,08
Art.-No.	123015	123039	123060	123077	123084	800206	800220	800244	

