


# STABILO® System

## Mobile Scaffold Series 10

- TÜV approved, max. load 200 kg/m<sup>2</sup> (scaffold class 3) according to EN1004
- Stable steel stabilizer ensures safe foothold when standing
- Vertically adjustable casters enable safe use on uneven ground
- The platform is vertically adjustable from rung to rung in 25 cm rung increments between the diagonal braces. Extensive reassembling and disassembling can be avoided
- Outriggers are included in the delivery contents for all scaffolds with a working height starting with 7.40 m
- Field lengths: 2.00 m and 2.50 m
- Scaffold platform width: 0.75 m



Art.-No. 731319



You can find System parts from page 84



Art.-No. 731357

**Important:** Depending of the mobile scaffold configuration, ballast weights must be used (accessories). For ballast weight specifications, please refer to the instructions for assembly and use or at our homepage.

73 10	Field length: 2,00 m - Scaffold field width: 0,75 m											
Working height ca. m <b>A</b>	3,00	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40	14,40
Standing height ca. m <b>B</b>	1,00	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40
Scaffold height ca. m <b>C</b>	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40
Total weight kg	49,0	98,0	106,0	117,0	161,0	172,0	195,0	207,0	234,0	246,0	253,0	264,0
Art.-No.	731302	731319	731326	731333	731340	731357	731364	731371	731388	731395	731401	731418

74 10	Field length: 2,50 m - Scaffold field width: 0,75 m											
Working height ca. m <b>A</b>	3,00	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40	14,40
Standing height ca. m <b>B</b>	1,00	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40
Scaffold height ca. m <b>C</b>	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40
Total weight kg	53,0	109,0	117,0	131,0	179,0	193,0	216,0	230,0	262,0	276,0	284,0	297,0
Art.-No.	741301	741318	741325	741332	741349	741356	741363	741370	741387	741394	741400	741417