


# STABILO® System

## Mobile Scaffold Series 50

- TUEV approved, load capacity 200 kg/m<sup>2</sup> (scaffold class 3) in accordance with EN1004
- The ideal scaffold for large-area works up to a working height of 14.00 m
- A heavy-duty steel cross bar provides firm foothold when standing
- The platform panels may be easily mounted (in increments of 25 cm) between the diagonal rods. No more reassembly or disassembly!
- The platform size of almost 4 m<sup>2</sup> offers a large and safe working space for personnel and materials
- The handy vertical frames can be easily mounted by one person only and the serrated rungs guarantee safe ascent and descent
- Extension arms are included in the delivery for all scaffolds with a working height of 6.40 m or above
- Field lengths: 2.00 m and 2.50 m
- Scaffold field width: 1.50 m



Art.-No. 735218



You can find System parts from page 84



Art.-No. 735256

**Important:** Depending of the mobile scaffold configuration, ballast weights must be used (accessories). For ballast weight specifications, please refer to the instructions for assembly and use or at our homepage.

73 50	Field length: 2,00 m - Scaffold field width: 1,50 m											
Working height ca. m <b>A</b>	3,00	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40	14,40
Standing height ca. m <b>B</b>	1,00	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40
Scaffold height ca. m <b>C</b>	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40
Total weight kg	72,0	133,0	145,0	193,0	239,0	255,0	266,0	282,0	328,0	344,0	356,0	371,0
Art.-No.	735201	735218	735225	735232	735249	735256	735263	735270	735287	735294	735300	735317

74 50	Field length: 2,50 m - Scaffold field width: 1,50 m											
Working height ca. m <b>A</b>	3,00	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40	14,40
Standing height ca. m <b>B</b>	1,00	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40
Scaffold height ca. m <b>C</b>	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40
Total weight kg	79,0	147,0	159,0	209,0	263,0	281,0	293,0	311,0	365,0	383,0	395,0	413,0
Art.-No.	745200	745217	745224	745231	745248	745255	745262	745279	745286	745293	745309	745316