


# STABILO® System

## Mobile Scaffold Series 500

- TUEV approved, load capacity 200 kg/m<sup>2</sup> (scaffold class 3) in accordance with EN1004
- The ideal scaffold for large-area works up to a working height of 14.00 m
- The platform panels may be easily mounted (in increments of 25 cm) between the diagonal rods. No more reassembly or disassembly!
- The platform size of almost 4 m<sup>2</sup> offers a large and safe working space for personnel and materials
- The handy vertical frames can be easily mounted by one person only and the serrated rungs guarantee safe ascent and descent
- Extension arms are included in the delivery for all scaffolds with a working height of 8.40 m or above
- Field lengths: 2.00 m, 2.50 m and 3.00 m
- Scaffold field width: 1.50 m

You can find System parts from page 84



**Important:** Depending of the mobile scaffold configuration, ballast weights must be used (accessories). For ballast weight specifications, please refer to the instructions for assembly and use or at our homepage.

73 500		Field length: 2,00 m - Scaffold field width: 1,50 m								
Working height	ca. m <b>A</b>	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40
Standing height	ca. m <b>B</b>	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40
Scaffold height	ca. m <b>C</b>	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40
Total weight	kg	151,0	166,0	178,0	224,0	275,0	287,0	302,0	348,0	364,0
Art.-No.		735058	735065	735072	735089	735096	735102	735119	735126	735133

74 500		Field length: 2,50 m - Scaffold field width: 1,50 m										
Working height	ca. m <b>A</b>	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40	14,40
Standing height	ca. m <b>B</b>	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40
Scaffold height	ca. m <b>C</b>	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40
Total weight	kg	165,0	183,0	195,0	249,0	303,0	315,0	333,0	387,0	405,0	417,0	435,0
Art.-No.		745057	745064	745071	745088	745095	745101	745118	745125	745132	745149	745156

75 500		Field length: 3,00 m - Scaffold field width: 1,50 m										
Working height	ca. m <b>A</b>	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40	14,40
Standing height	ca. m <b>B</b>	2,40	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40
Scaffold height	ca. m <b>C</b>	3,40	4,40	5,40	6,40	7,40	8,40	9,40	10,40	11,40	12,40	13,40
Total weight	kg	187,0	206,0	218,0	289,0	347,0	359,0	378,0	449,0	468,0	480,0	499,0
Art.-No.		755438	755537	755667	755766	755865	755964	755063	755162	755261	755360	755148