



STABILO®

Multi-Purpose Hinged Telescopic Ladder with 4 rail extensions

- Four-piece telescopic aluminum hinged ladder: Can be used as double-standing ladder, leaning ladder or as two separate double standing ladders with 4 integrated rail extensions (extendable up to 230 mm)
- The telescopic rung-to-rung displacement of the outer ladder parts from rung to rung (ClickMatic System) and the use of 4 integrated rail extensions ensure the usage on varying floor levels (stairs, steps and uneven surfaces)
- With a few adjustments, the inner and outer ladder parts can be converted into two separate double standing ladder which, equipped with a plank, can then be used as working table or trestle (Note: For this set-up, Combi stabilizer, Art.-No. 121417, must be used as lower enlargement of the inner ladder)
- Completely serrated rungs for safe ascent and descent
- The compact construction enables transport in cars
- Additional stability through corner braces in the bottom area
- Non-slip, 2-component footcaps: The hard component ensures a strong connection of the cap with the rail; the soft component provides a strong surface stiction and prevents slipping of the ladder



Art.-No. 123596



For the **CombiSystem** (Safety Accessories) and other accessories refer to page 112.
Suitable for this ladder:
CombiSystem
1, 2, 3, 4, 5, 6, 8



Work. height up to ca. m A	3,00	3,00
Work. height up to ca. m A1	3,60	4,15
Work. height up to ca. m A2	5,25	6,35
Length trestle ca. m B	2,05	2,55
Length, leaning lad. ca. m C	4,20	5,30
No. of rungs	4x4	4x5
Weight ca. kg	16,0	18,0
Transport dimensions	Length ca. m	1,35
	Width ca. m	0,69
	Height ca. m	0,20
Art.-No.	123589	123596

