MONTO

Multipurpose rung ladder Tribilo®

Three-section aluminium multipurpose ladder usable as a leaning, extension and freestanding ladder with an extendable ladder section.

+ Powder-coated steel guiding profiles for greater ease of use (size 3 x 14 with aluminium guiding profiles)
+ Self-locking levers (AutoSnap-System) for safe transport
+ Weather-resistant and tear-proof webbing straps as spread lock
+ Wide stabiliser for even greater stability
+ Slip-resistant foot caps and plugs (SafetyCap)
+ Pre-equipped with a wosatec QR code label for easy digitalisation of work equipment inspection documentation

The following ladders are suitable for use on stairs:
Art.-No. 129741 – 3 x 8 rungs
Art.-No. 129765 – 3 x 10 rungs
Art.-No. 129789 – 3 x 12 rungs

From size 3 x 12 rungs and above the removable ladder part can only be used with Trigon-Stabiliser.

wosatec Digital inspection app for work equipment
Info: Page 243



Number of rungs				3 x 9	3 x 10	3 x 12	3 x 14	suitable for use on stairs 3 x 8	3 x 10	3 x 12
1		**A** up to approx.	m	6.85	7.65	9.30	10.90	6.05	7.65	9.30
		B approx.	m	4.85	5.65	7.30	8.90	4.05	5.65	7.30
		C approx.	m	6.05	6.90	8.60	10.25	5.25	6.90	8.60
		D approx.	m	5.85	6.65	8.30	9.90	5.05	6.65	8.30
2		**A** up to approx.	m	4.95	5.45	6.55	7.60	4.40	5.45	6.55
		B approx.	m	2.95	3.45	4.55	5.60	2.40	3.45	4.55
		C approx.	m	4.40	4.95	6.05	7.20	3.80	4.95	6.05
		D approx.	m	4.20	4.70	5.70	6.90	3.65	4.70	5.70
3		**A** up to approx.	m	3.85	4.10	4.65	5.20	3.60	4.10	4.65
		B approx.	m	1.85	2.10	2.65	3.20	1.60	2.10	2.65
		C approx.	m	2.70	3.00	3.55	4.10	2.40	3.00	3.55
		D approx.	m	2.65	2.80	3.30	4.00	2.25	2.80	3.30
4		**A** up to approx.	m	3.60	3.85	4.40	4.95	3.35	3.85	4.40
		B approx.	m	1.60	1.85	2.40	2.95	1.35	1.85	2.40
		C approx.	m	2.70	3.00	3.55	4.10	2.40	3.00	3.55
		D approx.	m	2.60	2.85	3.40	4.00	2.35	2.85	3.40
5		**A** up to approx.	m	–	–	–	–	4.40	4.95	5.45
		B approx.	m	–	–	–	–	2.40	2.95	3.45
		C approx.	m	–	–	–	–	3.25	3.80	4.35
		D approx.	m	–	–	–	–	3.10	3.65	4.15
Stabiliser width approx.			m	1.00	1.15	1.25	1.25	0.90	1.15	1.25
Product weight approx.			kg	16.7	18.3	27.3	31.3	15.3	18.3	27.3
		Width (B) approx.	m	0.50	0.50	0.50	0.50	0.50	0.50	0.50
		Depth (T) approx.	m	0.20	0.20	0.25	0.25	0.20	0.20	0.25
		Length (L) approx.	m	2.70	3.00	3.55	4.10	2.45	3.00	3.55
Art.-No.				129673	129680	129703	129727	129741	129765	129789



Combi System							
	3x8–3x14	3x8–3x14	3x8–3x14	3x8–3x14	3x8–3x10	3x8–3x14	3x8–3x14
Page 100	①	②	③	④	⑤	⑥	⑧