



wosatec Digital inspection app for work equipment
Info: **Page 243**

STABILO® Professional

Plug-in ladder system with rungs

Easily stowable aluminium plug-in ladder system with rungs for different working heights.

+ Extruded aluminium side rails with reinforced edges for a maximum of stability and a long service life
+ High-strength rung/rail connection
+ Ladder base with wide stabiliser and slip-resistant foot caps (SafetyCap)
+ Top ladder part with wall castors and abrasion-resistant contact block made of soft rubber material with wedge cut-out which can be leaned against house corners and window profiles
+ Two-component top and foot plugs consisting of a hard and soft part with anti-slip/wall protection protect sensitive floors and facades or walls
+ Stable plug-in connection with automatic locking which does not protrude beyond the ladder rail and can be released again with one hand movement
+ Quick-release fasteners on the inside of the rail which do not disturb during transport and storage of the ladder
+ Round safety bolts also serve as guides for easy assembly of the ladder sections without wedging. They lock automatically when the ladder reaches its end position
+ The top ladder part ensures also individual use due to its two-component foot plugs and the contact block made of soft rubber material as anti-slip/wall protection and protects sensitive floors and facades or walls
+ Loadable up to 150 kg
+ Pre-equipped with a wosatec QR code label for easy digitalisation of work equipment inspection documentation

Plug-in ladder sets with rungs

			2-section sets		3-section sets		4-section sets	
								
Ladder combination			Lower, upper section	Lower, upper section	Lower, middle, upper section	Lower, middle, upper section	Lower, middle, middle, upper section	Lower, middle, middle, upper section
1	A up to approx.	m	3.60	4.35	4.90	5.65	6.20	6.95
	B approx.	m	1.60	2.35	2.90	3.65	4.20	4.95
2	C approx.	m	2.80	3.65	4.20	5.05	5.60	6.45
	D approx.	m	2.65	3.40	3.95	4.70	5.25	6.05
Width approx. (incl. stabiliser)		m	0.85	0.90	0.85	0.90	0.85	0.90
Product weight approx.		kg	8.6	10.4	13.0	14.8	17.4	19.2
Art.-No.			**842374**	**842343**	**842381**	**842350**	**842398**	**842367**

Single sections

Number of rungs		**2**	**5**	**5**	**5***
					
Ladder combination		**Lower section**	**Lower section**	**Middle section**	**Upper section**
Length approx.	m	0.85	1.65	1.70	2.30
Width approx. (incl. stabiliser)	m	0.85	0.90	0.45	0.45
Depth approx.	m	0.10	0.10	0.10	0.15
Product weight approx.	kg	2.8	4.6	4.4	5.8
Art.-No.		**842312**	**842305**	**842329**	**842336**

*upper rung not usable