

## Rope-operated three-section rung ladder

A three-section rope-operated ladder for professional use at great heights with wall castors for maximum ease when extending the ladder.

- + Height-adjustment by two ropes
- + Middle and top section can be height-adjusted rung by rung
- + Automatic-locking arrestor for a maximum of safety
- + Incl. wall castors for a comfortable extension and retraction of the ladder
- + Extra wide stabiliser for even greater stability



To avoid the risk that a ladder will turnover while adjusting, it is recommended to use always a rope-operated ladder instead of an extension ladder. (Abstract of DGUV Information 208-016)



Number of rungs			3 x 14	3 x 16	3 x 18
1		A up to approx.	m 9.75	m 11.35	m 12.95
		B approx.	m 7.75	m 9.35	m 10.95
		C approx.	m 9.05	m 10.75	m 12.45
		D approx.	m 8.75	m 10.40	m 12.00
2		A up to approx.	m 4.85	m 5.40	m 5.95
		B approx.	m 2.85	m 3.40	m 3.95
		C approx.	m 4.10	m 4.90	m 5.30
		D approx.	m 3.90	m 4.45	m 4.95
Stabiliser width approx.		m	1.20	1.20	1.20
Product weight approx.		kg	45.0	51.0	56.6
	Width (B) approx.	m	0.50	0.50	0.50
	Depth (T) approx.	m	0.25	0.25	0.25
	Length (L) approx.	m	4.10	4.90	5.30
Art.-No.			800756	800763	800770

