



MONTO[®]

Multipurpose rung ladder

Two section aluminium multipurpose ladder usable as a step ladder, leaning and extension ladder

- + Powder-coated steel guiding profiles for easier handling
- + Longlasting 32-times beaded rung/side rail connections
- + Extra wide stabiliser for a maximum of safety
- + Anti-slip foot caps (Safety Cap)
- + Spreader braces made of weather resistant and tear-proof straps
- + Self-locking levers for a safe transport (AutoSnap-System)





Nu	umber of rungs						2 x 9	:	2 x 12
1	A B C D	A up to	approx.	in	n m		5.25		6.85
		В	approx.	in	n m		3.25		4.85
		С	approx.	in	n m		4.35		6.05
		D	approx.	in	n m		4.20		5.85
	A B C D	A up to	approx.	in	n m		3.85		4.65
2		В	approx.	in	n m		1.85		2.65
		С	approx.	in	n m		2.70		3.50
		D	approx.	in	n m		2.55		3.35
	ABC	A up to approx.		in	n m		3.60		4.40
3		В	approx.	in	n m		1.60		2.40
3		С	approx.	in	n m		2.70		3.50
		D	approx.	in	n m		2.60		3.40
Pr	Product weight approx.			in	kg		9.7		14.1
		Width	(B) approx.	in	n m		0.41		0.41
Depth (T) approx. Length (L) approx.		in	n m		0.12		0.14		
		Length	(L) approx.	in	n m		2.70		3.55
Ar	ticle No.					1	20571	1	20588



















Combi-Safety accessories (Aluminium)

Step / Tray

- + Suitable for ladders with rungs for more safety and comfort
- + Usable as a tray for all kind of items when working on rung ladders
- + Can hold up to 150 kg
- + TÜV-approved





Ladder spikes (Pair)

- + According to the German Statuatory Accident Insurance Body ladders used on natural soft ground have to be equipped with spikes
- + Also usable with ladders with stabilisers

Article No.

121400

- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved





Article No. 122063


Side rail extensions

- + To compensate height differences such as stairs, curbs etc.
- + Infinitely adjustable up to max. 600 mm
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Spacer device

- Usable in areas with difficult access e.g. ledges, overhanging roofs
- Telescopic supports, extendable up to 600 mm
- Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved





Article No.
122292

Stabiliser

- + To compensate height differences up to 17 cm on stairs/ledges etc.
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved





Cross Rail levellers

+ To compensate height differences when using stabilisers on stairs, ledges or uneven ground and for a maximum of stability (extension range up to 230 mm)

Article No. 122018

- + Suitable for all ladders with stabilisers
- + TÜV-approved



Article No.
121417

MultiBoard

- + To be used in combination with multipurpose hinged ladders to create a working platform or a placement area
- + Anti-slip and waterproof working platform suitable for a max. load of 150 kg







1.3	122285

Wall Holder Set

- + For safe and space-saving storage of ladders with rungs
- + Lockable (Lock not included)
- + Internal dimensions: 270 x 150 mm





Article No
100061

Article No.	
122460	