

MONTO®

Rope-operated two section rung ladder Robilo®

A rope-operated aluminium ladder for easy height adjustment

- + Easy to use rope guided for a high functionality
- + Can be height-adjusted rung by rung
- + Sturdy powder-coated steel guiding profiles for easier handling
- + Incl. wall castors for ladders 2 x 18 for a comfortable extension and retraction of the ladder
- + Anti-slip foot caps (Safety Cap)



Number of rungs			2 x 15	2 x 18	
1		A up to approx.	in m	8.45	9.80
		B approx.	in m	6.45	7.80
		C approx.	in m	7.70	9.10
		D approx.	in m	7.45	8.80
2		A up to approx.	in m	5.25	6.05
		B approx.	in m	3.25	4.05
		C approx.	in m	4.35	5.20
		D approx.	in m	4.20	5.00
Product weight approx.		in kg	19.5	26.5	
	Width (B) approx.	in m	0.41	0.43	
	Depth (T) approx.	in m	0.13	0.16	
	Length (L) approx.	in m	4.40	5.20	
Article No.			120663	120670	

Combi-Safety accessories (Aluminium)

Step / Tray


- + Suitable for ladders with rungs for more safety and comfort
- + Usable as a tray for all kind of items when working on rung ladders
- + Can hold up to 150 kg
- + TÜV-approved



Article No.
122063

Ladder spikes (Pair)

- + According to the German Statutory Accident Insurance Body ladders used on natural soft ground have to be equipped with spikes
- + Also usable with ladders with stabilisers
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Article No.
121400


Side rail extensions

- + To compensate height differences such as stairs, curbs etc.
- + Infinitely adjustable up to max. 600 mm
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Spacer device

- + Usable in areas with difficult access e.g. ledges, overhanging roofs
- + Telescopic supports, extendable up to 600 mm
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved




Article No.
122292

Article No.
122018

Stabiliser

- + To compensate height differences up to 17 cm on stairs/ledges etc.
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Cross Rail levellers

- + To compensate height differences when using stabilisers on stairs, ledges or uneven ground and for a maximum of stability (extension range up to 230 mm)
- + Suitable for all ladders with stabilisers
- + TÜV-approved



Article No.
121417

Weight kg
1.3

Article No.
122285

MultiBoard

- + To be used in combination with multi-purpose hinged ladders to create a working platform or a placement area
- + Anti-slip and waterproof working platform suitable for a max. load of 150 kg



Article No.
122261

Wall Holder Set

- + For safe and space-saving storage of ladders with rungs
- + Lockable (Lock not included)
- + Internal dimensions: 270 x 150 mm



Article No.
122469