

STABILO®

Professional

Double-sided rung ladder

A sturdy aluminium rung ladder for an easy and flexible use

- + Screwed hinge connections and strap links
- + Anti-slip rungs with a depth of 30 mm, profiled on all sides
- + Anti-slip foot caps (Safety Cap)
- + Longlasting 32-times beaded rung/side rail connections
- + 4 reinforced corners for a maximum of stability
- + Safety clips for safe transport



SafetyCap



Number of rungs			2 x 6	2 x 7	2 x 8	2 x 10	2 x 12	2 x 14	2 x 16	2 x 18	
1	A	up to approx.	in m	3.05	3.30	3.55	4.10	4.60	5.10	5.75	6.25
	B	approx.	in m	1.05	1.30	1.55	2.10	2.60	3.10	3.75	4.25
2	C	approx.	in m	1.80	2.05	2.35	2.90	3.45	4.05	4.60	5.15
	D	approx.	in m	1.65	1.95	2.20	2.70	3.25	3.75	4.40	4.95
Product weight approx.			in kg	6.3	7.5	8.5	10.7	13.5	16.5	19.5	22.5
Width (B) approx.			in m	0.57	0.59	0.63	0.69	0.70	0.82	0.85	0.91
Depth (T) approx.			in m	0.14	0.14	0.14	0.14	0.14	0.14	0.15	0.15
Length (L) approx.			in m	1.80	2.10	2.40	2.95	3.50	4.05	4.60	5.15
Article No.				124906	124913	124920	124937	124944	124951	1801746	801753



Accessories:



Conductive foot end plugs



Pay attention to this label!

All products marked with this label are already approved after production and will facilitate documentation work.



Conductive foot plugs (pair)

- + Resistance < 106 Ω /m
- + Conforms to DIN EN 13463-1

Side rail dimensions	Article No.
64 x 25	212597
77 x 25	212603
97 x 25	212610



Conductive foot caps for stabilisers

- + Resistance < 106 Ω /m
- + Conforms to DIN EN 13463-1

Side rail dimensions	Article No.
64 x 25	212627

