

# STABILO® Professional

## Mobile double-sided standing step ladder

This mobile double-sided aluminium standing step ladder is extremely easy to handle and to transport.

- + High-strength beaded step/side rail connections
- + Integrated pull and push protecting device for a maximum of safety
- + Anti-slip foot caps (Safety Cap)
- + 4 retractable spring castors (RollStop-System)

**i** According to the German Statutory Accident Insurance Body and its Guideline BGI 694, all mobile step ladders have to be equipped with a pull and push protection device before use.



Number of steps			2 x 3	2 x 4	2 x 5	2 x 6	2 x 7	2 x 8	2 x 10	2 x 12	
1	<b>A</b>	up to approx.	in m	2.25	2.50	2.70	2.95	3.20	3.40	3.90	4.35
	<b>B</b>	approx.	in m	0.25	0.50	0.70	0.95	1.20	1.40	1.90	2.35
2	<b>C</b>	approx.	in m	0.80	1.05	1.30	1.55	1.80	2.05	2.55	3.05
	<b>D</b>	approx.	in m	0.70	0.95	1.20	1.40	1.65	1.90	2.35	2.80
Product weight approx.			in kg	6.5	7.7	9	10.3	11.6	12.9	16.3	19.4
Width (B) approx.			in m	0.61	0.64	0.67	0.70	0.73	0.76	0.82	0.86
Depth (T) approx.			in m	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Length (L) approx.			in m	0.80	1.05	1.30	1.55	1.80	2.05	2.55	3.05
Article No.				124814	124821	124838	124845	124852	124869	124876	124883

### Accessories:

- Conductive foot end plugs





**Pay attention to this label!**

All products marked with this label are already approved after production and will facilitate documentation work.



**Conductive foot plugs (pair)**

- + Resistance < 106  $\Omega$ /m
- + Conforms to DIN EN 13463-1

Side rail dimensions	Article No.
64 x 25	<b>212597</b>
77 x 25	<b>212603</b>
97 x 25	<b>212610</b>



**Conductive foot caps for stabilisers**

- + Resistance < 106  $\Omega$ /m
- + Conforms to DIN EN 13463-1

Side rail dimensions	Article No.
64 x 25	<b>212627</b>

