

STABILO®
Professional

Rope-operated three section rung ladder

Three section rope-operated aluminium ladder for working at higher levels

- + Height-adjustment by two ropes
- + Middle and top section can be height-adjusted rung by rung
- + Automatic-locking arrestor for a maximum of safety
- + Incl. wall castors for a comfortable extension and retraction of the ladder



To avoid the risk that a ladder will turnover while adjusting it is recommended by the German Statutory Accident Insurance Body to use always a rope-operated ladder instead of an extension ladder. (Abridgement of the Guideline BGI 694)



Number of rungs			3 x 14	3 x 16	3 x 18	
1		A up to approx.	in m	9.75	11.35	12.95
		B approx.	in m	7.75	9.35	10.95
		C approx.	in m	9.05	10.75	12.45
		D approx.	in m	8.75	10.40	12.00
2		A up to approx.	in m	4.85	5.40	5.95
		B approx.	in m	2.85	3.40	3.95
		C approx.	in m	4.05	4.60	5.15
		D approx.	in m	3.90	4.45	4.95
Product weight approx.		in kg	45.0	51.0	56.6	
	Width (B) approx.	in m	0.48	0.48	0.48	
	Depth (T) approx.	in m	0.25	0.25	0.25	
	Length (L) approx.	in m	4.10	4.90	5.30	
Article No.			810007	810014	810021	

Combi
system



①



②



③



④



⑤



⑥



⑧

Accessories:



Conductive foot end plugs





Pay attention to this label!

All products marked with this label are already approved after production and will facilitate documentation work.



Conductive foot plugs (pair)

- + Resistance < 106 Ω/m
- + Conforms to DIN EN 13463-1

Side rail dimensions	Article No.
64 x 25	212597
77 x 25	212603
97 x 25	212610



Conductive foot caps for stabilisers

- + Resistance < 106 Ω/m
- + Conforms to DIN EN 13463-1

Side rail dimensions	Article No.
64 x 25	212627



Combi-Safety accessories (Aluminium)

Step / Tray


- + Suitable for ladders with rungs for more safety and comfort
- + Usable as a tray for all kind of items when working on rung ladders
- + Can hold up to 150 kg
- + TÜV-approved



Article No.
122063

Ladder spikes (Pair)

- + According to the German Statutory Accident Insurance Body ladders used on natural soft ground have to be equipped with spikes
- + Also usable with ladders with stabilisers
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Article No.
121400


Side rail extensions

- + To compensate height differences such as stairs, curbs etc.
- + Infinitely adjustable up to max. 600 mm
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Spacer device

- + Usable in areas with difficult access e.g. ledges, overhanging roofs
- + Telescopic supports, extendable up to 600 mm
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved




Article No.
122292

Article No.
122018


Stabiliser

- + To compensate height differences up to 17 cm on stairs/ledges etc.
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Cross Rail levellers

- + To compensate height differences when using stabilisers on stairs, ledges or uneven ground and for a maximum of stability (extension range up to 230 mm)
- + Suitable for all ladders with stabilisers
- + TÜV-approved



Article No.
121417

Weight kg
1.3

Article No.
122285

MultiBoard

- + To be used in combination with multi-purpose hinged ladders to create a working platform or a placement area
- + Anti-slip and waterproof working platform suitable for a max. load of 150 kg



Article No.
122261

Wall Holder Set

- + For safe and space-saving storage of ladders with rungs
- + Lockable (Lock not included)
- + Internal dimensions: 270 x 150 mm



Article No.
122469