

STABILO® Professional






Single section leaning step ladder

A multipurpose aluminium leaning ladder developed for a maximum of comfort and stability.

- + Extremely safe due to its integrated anti-slip/wall protector
- + Extruded aluminium side rails with reinforced corners for a maximum of stability and a long lifetime
- + High-strength beaded step/side rail connections
- + Easy to ascend with a comfortable stand on profiled rungs with a depth of 80 mm
- + Anti-slip foot caps (Safety Cap)

i A safe ascending and descending can easily be increased by fitting an additional hand rail and ladder hooks to the ladder (see page 65/66).



| Number of steps | | | 6 | 7 | 8 | 10 | 12 | 15 | |
|---|---|---------------|-------|--------|--------|--------|--------|--------|--------|
| 1 |  A | up to approx. | in m | 2.70 | 2.90 | 3.15 | 3.60 | 4.10 | 4.80 |
| |  B | approx. | in m | 0.70 | 0.90 | 1.15 | 1.60 | 2.10 | 2.80 |
| 2 |  C | approx. | in m | 1.70 | 1.95 | 2.20 | 2.70 | 3.20 | 3.95 |
| |  D | approx. | in m | 1.60 | 1.80 | 2.05 | 2.50 | 3.00 | 3.70 |
| Product weight approx. | | | in kg | 3.6 | 4.2 | 4.8 | 6.0 | 7.2 | 9.0 |
|  | Width (B) approx. | | in m | 0.38 | 0.38 | 0.38 | 0.38 | 0.38 | 0.38 |
| | Depth (T) approx. | | in m | 0.10 | 0.10 | 0.10 | 0.10 | 0.10 | 0.10 |
| | Length (L) approx. | | in m | 1.70 | 1.95 | 2.20 | 2.70 | 3.20 | 3.95 |
| Article No. | | | | 124401 | 124418 | 124425 | 124432 | 124449 | 124456 |

Accessories:



②

③

④

⑤

⑥

⑧



Pay attention to this label!

All products marked with this label are already approved after production and will facilitate documentation work.



Conductive foot plugs (pair)

- + Resistance < 106 Ω/m
- + Conforms to DIN EN 13463-1

| Side rail dimensions | Article No. |
|----------------------|---------------|
| 64 x 25 | 212597 |
| 77 x 25 | 212603 |
| 97 x 25 | 212610 |



Conductive foot caps for stabilisers

- + Resistance < 106 Ω/m
- + Conforms to DIN EN 13463-1

| Side rail dimensions | Article No. |
|----------------------|---------------|
| 64 x 25 | 212627 |



Combi-Safety accessories (Aluminium)

Step / Tray


- + Suitable for ladders with rungs for more safety and comfort
- + Usable as a tray for all kind of items when working on rung ladders
- + Can hold up to 150 kg
- + TÜV-approved



| |
|-------------|
| Article No. |
| 122063 |

Ladder spikes (Pair)

- + According to the German Statutory Accident Insurance Body ladders used on natural soft ground have to be equipped with spikes
- + Also usable with ladders with stabilisers
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



| |
|-------------|
| Article No. |
| 121400 |


Side rail extensions

- + To compensate height differences such as stairs, curbs etc.
- + Infinitely adjustable up to max. 600 mm
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Spacer device

- + Usable in areas with difficult access e.g. ledges, overhanging roofs
- + Telescopic supports, extendable up to 600 mm
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved




| |
|-------------|
| Article No. |
| 122292 |

| |
|-------------|
| Article No. |
| 122018 |


Stabiliser

- + To compensate height differences up to 17 cm on stairs/ledges etc.
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Cross Rail levellers

- + To compensate height differences when using stabilisers on stairs, ledges or uneven ground and for a maximum of stability (extension range up to 230 mm)
- + Suitable for all ladders with stabilisers
- + TÜV-approved



| |
|-------------|
| Article No. |
| 121417 |

| |
|-----------|
| Weight kg |
| 1.3 |

| |
|-------------|
| Article No. |
| 122285 |

MultiBoard

- + To be used in combination with multi-purpose hinged ladders to create a working platform or a placement area
- + Anti-slip and waterproof working platform suitable for a max. load of 150 kg



Wall Holder Set

- + For safe and space-saving storage of ladders with rungs
- + Lockable (Lock not included)
- + Internal dimensions: 270 x 150 mm



| |
|-------------|
| Article No. |
| 122261 |

| |
|-------------|
| Article No. |
| 122469 |