


STABILO®
Professional

Two section extension rung ladder

An extremely stable two section aluminium extension ladder for professional use

- + Sturdy, rail surrounding aluminium guiding profiles for a maximum of stability
- + Automatic locking levers (AutoSnap System) for a safe transport
- + Sturdy extruded aluminium side rails with reinforced corners
- + Anti-slip rungs with a depth of 30 mm, profiled on all sides for a maximum of safety
- + Can be used as a 1 or 2 section ladder



Number of rungs			2 x 9	2 x 12	2 x 15	2 x 18	
1	A	up to approx.	in m	5.25	6.85	8.45	9.85
	B	approx.	in m	3.25	4.85	6.45	7.85
	C	approx.	in m	4.35	6.05	7.75	9.15
	D	approx.	in m	4.20	5.85	7.45	8.80
2	A	up to approx.	in m	3.60	4.40	5.25	6.05
	B	approx.	in m	1.60	2.40	3.25	4.05
	C	approx.	in m	2.70	3.55	4.35	5.20
	D	approx.	in m	2.60	3.40	4.25	5.05
Product weight approx.			in kg	9	13.5	18	25.5
	Width (B) approx.		in m	0.43	0.43	0.43	0.43
	Depth (T) approx.		in m	0.12	0.14	0.14	0.18
	Length (L) approx.		in m	2.70	3.55	4.40	5.25
Article No.				123121	123145	123169	123176

Accessories:



Conductive foot end plugs

Combi System



①



②



③



④



⑤



⑥



⑧





Pay attention to this label!

All products marked with this label are already approved after production and will facilitate documentation work.



Conductive foot plugs (pair)

- + Resistance < 106 Ω /m
- + Conforms to DIN EN 13463-1

Side rail dimensions	Article No.
64 x 25	212597
77 x 25	212603
97 x 25	212610



Conductive foot caps for stabilisers

- + Resistance < 106 Ω /m
- + Conforms to DIN EN 13463-1

Side rail dimensions	Article No.
64 x 25	212627



Combi-Safety accessories (Aluminium)

Step / Tray


- + Suitable for ladders with rungs for more safety and comfort
- + Usable as a tray for all kind of items when working on rung ladders
- + Can hold up to 150 kg
- + TÜV-approved



Article No.
122063

Ladder spikes (Pair)

- + According to the German Statutory Accident Insurance Body ladders used on natural soft ground have to be equipped with spikes
- + Also usable with ladders with stabilisers
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Article No.
121400

Side rail extensions


- + To compensate height differences such as stairs, curbs etc.
- + Infinitely adjustable up to max. 600 mm
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Article No.
122292

Spacer device


- + Usable in areas with difficult access e.g. ledges, overhanging roofs
- + Telescopic supports, extendable up to 600 mm
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Article No.
122018

Stabiliser

- + To compensate height differences up to 17 cm on stairs/ledges etc.
- + Suitable for side rails with a width of 64 x 25 mm to 97 x 25 mm
- + TÜV-approved



Article No.
121417

Cross Rail levellers

- + To compensate height differences when using stabilisers on stairs, ledges or uneven ground and for a maximum of stability (extension range up to 230 mm)
- + Suitable for all ladders with stabilisers
- + TÜV-approved



Weight kg
1.3

Article No.
122285

MultiBoard

- + To be used in combination with multi-purpose hinged ladders to create a working platform or a placement area
- + Anti-slip and waterproof working platform suitable for a max. load of 150 kg



Article No.
122261

Wall Holder Set

- + For safe and space-saving storage of ladders with rungs
- + Lockable (Lock not included)
- + Internal dimensions: 270 x 150 mm



Article No.
122469