



Mobile stairs with platform (Light metal)

Sturdy aluminium stair, the safe and mobile work equipment for a wide range of workspaces, produced in accordance with DIN EN ISO 14122

- + Step width: 600 – 800 – 1000 mm
- + Step depth 225 mm for work inclination 45° and 175 mm for 60°
- + Aluminium grating or aluminium perforated surfaces are available on request
- + Platform extensions in width or length are available on request
- + Supplied with hand rails on both sides and three-sided platform railing with a height of 1100 mm with knee rail and foot rail
- + Railing on stairs with a work inclination of 45° are fitted with a knee rail and a foot rail
- + 2 braked guiding castors Ø 160 mm at the supporting part and 2 braked guided castors Ø 160 mm at the ascending part
- + Sturdy stabiliser with castors at supporting part
- + All stairs are supplied in pre-assembled modules
- + Stairs with other work inclinations, step widths and surfaces are available on request
- + * In accordance with DIN EN ISO 14122 stairs and crossovers with a vertical height of 500 mm and more and a gap at the side of > 200 mm have to be equipped with a second hand rail

Optional accessories for these stairs:

- + Safety barrier
- + Safety gate
- + Removable tool tray
- + Plug-in rail
- + Anti-slip rail
- + Safety chain
- + Colour marked step edges
- + Central brake

Work inclination 45°

| Number of steps | | 4 | 6 | 8 | 10 | 12 | 14 | 16 | 18 |
|-------------------------------|-------|----------------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Vertical height (A) | in mm | 646-860 | 1076-1290 | 1506-1720 | 1936-2150 | 2366-2580 | 2796-3010 | 3226-3440 | 3656-3870 |
| Projection (R) | in mm | 1227-1441 | 1657-1871 | 2087-2301 | 2516-2731 | 2947-3161 | 3376-3591 | 3807-4021 | 4237-4451 |
| Width of chassis with castors | in m | 1.10 | 1.10 | 1.40 | 1.40 | 1.60 | 1.60 | 1.80 | 1.80 |
| Type of step | | Aluminium corrugated | | | | | | | |
| Article No. Step width 600 | in mm | 827838 | 827852 | 827876 | 827890 | 827913 | 827937 | 827951 | 827975 |
| Article No. Step width 800 | in mm | 828033 | 828057 | 828071 | 828095 | 828118 | 828132 | 828156 | 828170 |
| Article No. Step width 1000 | in mm | 828231 | 828255 | 828279 | 828293 | 828316 | 828330 | 828354 | 828378 |

Work inclination 60°

| Number of steps | | 4 | 6 | 8 | 10 | 12 | 14 | 16 | 18 |
|-------------------------------|-------|----------------------|-----------|-----------|-----------|-----------|-----------|-----------|------------|
| Vertical height (A) | in mm | 751-1000 | 1251-1500 | 1751-2000 | 2251-2500 | 2751-3000 | 3251-3500 | 3751-4000 | 4251-4500* |
| Projection (R) | in mm | 1073-1216 | 1362-1505 | 1650-1794 | 1939-2082 | 2228-2371 | 2517-2660 | 2806-2949 | 3094-3238 |
| Width of chassis with castors | in m | 1.10 | 1.40 | 1.40 | 1.60 | 1.80 | 1.80 | 2.00 | 2.00 |
| Type of step | | Aluminium corrugated | | | | | | | |
| Article No. Step width 600 | in mm | 828637 | 828651 | 828675 | 828699 | 828712 | 828736 | 828750 | 828774 |
| Article No. Step width 800 | in mm | 828835 | 828859 | 828873 | 828897 | 828910 | 828934 | 828958 | 828972 |
| Article No. Step width 1000 | in mm | 829030 | 829054 | 829078 | 829092 | 829115 | 829139 | 829153 | 829177 |

Other finishes of steps and platforms*

| Step width | in mm | 600 | 800 | 1000 |
|------------------|-------------|--------|--------|--------|
| Steel grated | Article No. | 823908 | 823915 | 823922 |
| Steel perforated | Article No. | 823939 | 823946 | 823953 |

*Additional charge per step

Platform extension

| Step width | in mm | 600 | 800 | 1000 |
|---|-------------|--------|--------|--------|
| Platform extension, aluminium, per 225 mm | Article No. | 825704 | 825711 | 825728 |
| Rail extension, per 225 mm | Article No. | 825735 | 825735 | 825735 |