




STABILO®

Hinged Combination Ladder

- Four-piece aluminum ladder system which is adaptable to various working conditions
- The 2x3 and 2x6 rung ladders may be joined into many positions or can be used independently, for instance as work platform, leaning ladder, free-standing ladder, stairs ladder or multi-purpose ladder
- Convenient transport, as the ladder parts fold down to a compact unit and require only minimal storage space
- The patented KRAUSE safety lock hinge system with one-hand release bar ensures the quick and safe ladder functioning through the simultaneously unlocking of the hinges with only one hand
- The extruded aluminum rails are additionally reinforced at high-stress points for high profile stiffness and edge protection
- Wide-span horizontal stabilizer bar with 2-component foot caps enlarges the standing area
- Non-slip, 2-component foot caps: The hard component ensures strong link between cap and strut, the soft component provides a strong surface grip and prevents slipping of the ladder on smooth surfaces



Accessories:
 Power
 discharging foot
 caps, see
 page 113



Certificate
EN 131
 Norm



Work. height up to ca. m A	2,50	
Work. height up to ca. m A1	3,30	
Work. height up to ca. m A2	2,80	
Work. height up to ca. m A3	3,60	
Work. height up to ca. m A4	5,75	
Length trestle ca. m B	0,95/1,75	
Length trestle ca. m B1	2,85	
Length, leaning lad. ca. m C	4,65	
No. of rungs	2x3 + 2x6	
Weight ca. kg	15,0	
Transport dimensions	Length ca. m	1,85
	Width ca. m	0,42
	Height ca. m	0,19
Art.-No.	123558	

For the **CombiSystem** (Safety Accessories) and other accessories refer to page 112.
 Suitable for this ladder:
CombiSystem 1, 2, 3, 4, 5, 6, 8

